

Long-range readers XMP-TSG-60V



Dear Sirs,

as of now we can offer a long-range RFID reader TSG-60V with a range of up to 8 meter. This reader can be operated directly from the K24P/K32/K32Lite door controller using a special AUTEC identification and is suitable for vehicle detection by RFID.

Order-No.	Description
XMP-TSG-60V	<p>TSG-60V (Deister), Proximity reader for usage with door controller K32/K32Lite.</p> <p>Technical data: Reading distance: app. 8 meter Dimensions (WxHxD): 295x170x76 mm Color: silver Transmitter frequency: 2,45 GHz +/- 3,8 MHz Badge: Deister TPG 50x1-Card</p>

Errors and changes excepted.

Datei: M:\AUTEC Aktuell\2007e\doc\Akt0607e_op.doc

Order-No.	Description
XMP-TSG-60V-RA6	TSG60V Interface converter RS485 on RS232 to the setup of the reader. Unique necessarily!
XMP-TSG-60V-LRM1	LRM1 Wall holder for the long range reader TSG-60V
XMP-TSG-60V-LRM2	LRM2 Pylon holder for the long range reader TSG-60V
XMP-TPG-CH4	CH4 Badge holder with suction cup
XMP-TPG-5001	TPG-5001 Transponder fixed codes for car mounting.
XMP-TPG-5051	TPG-5051 Transponder programs after customer default for car mounting.

If you have any further questions, please do not hesitate to contact us.

With kind regards from Rheinland-Pfalz

Your AUTEC - Team

Errors and changes excepted.

Datei: M:\AUTEC Aktuell\2007e\doc\Akt0607e_op.doc